

### **BEST AVAILABLE COPY**

# PATENT ABSTRACTS OF JAPAN

(11)Publication number:

08-197853

(43) Date of publication of application: 06.08.1996

(51)Int.CI.

B41M 5/36

C09K 9/02

(21)Application number: 07-037001

(71)Applicant: TOSHIBA CORP

(22)Date of filing:

24.02.1995

(72)Inventor: NAITO KATSUYUKI

SUGIUCHI MASAMI

TAKAYAMA AKIRA

MIYAMOTO HIROHISA

NISHIZAWA HIDEYUKI

**FUJIOKA SAWAKO** 

WATANABE AKIKO

**NOMAKI TATSUO** 

(30)Priority

Priority number: 06 31046

6 31046 Priority date: 01.03.1994

Priority country: JP

06266394

31.10.1994

06287602

22.11.1994

JP


JP

#### (54) THERMOSENSIBLE RECORDING MEDIUM AND RECORDING METHOD

## (57)Abstract:

PURPOSE: To obtain a rewritable recording medium having a high contrast ratio in its coloring and fading conditions and capable of utilizing the background indication by including a coloration compound and a developer having a higher glass transit temperature than an ordinary temperature, and conducting recording and erasing of information based upon the reversible crystalline and non-crystalline substance.

CONSTITUTION: This medium includes a coloration compound and a developing agent having a glass transition temperature of 25°C or higher, and recording and erasing operations of information are conducted on the basis of a reversible transit of a crystalline and a non-



crystalline states. In addition, blending a matrix agent for lowering the density of the coloration compound and the developer agent allows the enhanced achievement of contrast. Since a much blending quantity of the developer agent is set, the temperature is effective in order for decreasing an energy quantity to be supplied for dissolving the recording material. At a room temperature Trt, the phases of the coloration compound A and developer agent B and the phase of the reversing agent C are separated, and in a coloring condition, the system loses its color in a higher heating condition than the melting point of Tm, and rapidly cooled and then solidified. On the contrary, the system becomes a coloring condition as it is heated higher than the glass transition temperature Tq.

#### LEGAL STATUS

[Date of request for examination]

11.07.1997

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

3176018

[Date of registration]

06.04.2001

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Copyright (C): 1998,2003 Japan Patent Office